

**Case A
323.11**

Model No. : 223、323 SERIES
Outline :

- All series are liquid-filled.
- Water-proof, shock resistant, and closed structures are durable and accurate, good for long time running.
- Special materials of movement and bourdon tube have lasting durabilities.
- It is applicable to the places of both strong fluctuation and non-corrosive fluid, such as air, water and oil.

Features :

- Model** : 223 series. (Push Twist Removable Bezel-RB)
323 series. (Crimped on Bezel-CB)
- Type** : Pressure gauge、Vacuum gauge、Compound gauge.
- Nominal Size** : 60mm.
- Case** : Stainless steel AISI 304 supplied with LM, CBM or LBM mount type and blowout disk on the top.
- Tubing** : Brass or Phosphor Bronze(upon request).
- Movement** : Brass.
- Connection** : Brass, 1/4", 3/8", NPT、PT、PF.
- Pointer Type** : General(Selective Adjustable Pointer)
- Accuracy** : $\pm 1.5\% \text{ F.S. (READ ANSI-B40.1 1985)}$
- Scale** : psi, bar, kPa, MPa, Kg/cm² etc. (Single or Dual Scale)

Note :

- LM : Lower Mount.
- CBM : Center Back Mount.
- LBM : Lower Back Mount.

Specifications :

Nominal size (mm)	Case	Connection	Model No.	Case Accessory
60	A	NPT、PT、PF (1/4", 3/8")	223.11	—
			323.11	—
	B		223.21	—
			323.21	—
			323.41	—
			323.51	—
			323.61	—
			323.71	—
			323.81	L Clamps
			323.91	U Bracket

Ranges (Kg/cm ²)	Socket	Tube	Accuracy (%F.S.)	Others
cmHg 76 cmHg	Brass	Brass or Phosphor Bronze	± 1.5	<ul style="list-style-type: none"> • Case & Ring 304 St. St. • Window Glass Acrylic (ASA LENS) • Liquid Filled Glycerine Silicon
0				
1				
2				
3				
4				
6				
11				
15				
20				
25				
35				
50				
70				
100				
150				
250				
350				
500				
700				
1000				