

**Case A
325.13**


Model No. : 225、325 SERIES

Outline :

- All series are liquid-filled.
- All series are stainless steel products with water proof, and closed structures which are capable against acidity, alkalinity, and corrosion. It is durable and accurate, good for long time running.
- Special materials of movement and bourdon tube have lasting durabilities.
- Specially it is applicable for corrosive fluid and strong fluctuation.

Features :

Model	: 225 series. (Push Twist Removable Bezel-RB) 325 series. (Crimped on Bezel-CB)
Type	: Pressure gauge、Vacuum gauge、Compound gauge.
Nominal Size	: 100mm.
Case	: Stainless steel AISI 304 supplied with LM, CBM or LBM mount type and blowout disk on the top.
Tubing	: Stainless steel AISI 316.
Movement	: Stainless steel AISI 304.
Connection	: Stainless steel AISI 304、316、1/4"、3/8"、1/2", NPT、PT、PF.
Pointer Type	: General(Selective Adjustable Pointer).
Accuracy	: $\pm 1.5\%$ F.S. (READ ANSI-B40.1 1985)
Scale	: psi, bar, kPa, MPa, Kg/cm ² etc. (Single or Dual Scale)

Note :

- LM : Lower Mount.
- CBM : Center Back Mount.
- LBM : Lower Back Mount.

Specifications :

Nominal size (mm)	Case	Connection	Model No.	Case Accessory
100	A	NPT、PT、PF (1/4"、3/8" 、1/2")	225.13	
			325.13	
	B		225.23	
	Back Flange		325.23	
			325.43	
			325.53	
			325.63	
			325.73	
	D		325.83	L Clamps
	Front Flange		325.73	
	Fixed Strap		325.83	U Bracket
			325.93	

Ranges (Kg/cm ²)	Corrosion Proof		Accuracy (%F.S.)	Others
	Socket	Tube		
cmHg 76 cmHg				· Case & Ring 304 St. St.
0~				
1				
2				
3				
4				
6				
10				
15				
20				
0~				· Window Glass Acrylic (ASA LENS)
1				
2				
3				
4	S.S.304	S.S.316	± 1.5	
6	S.S.316			
10				
15				
20				
25				
35				
50				
70				
100				
150				
250				
350				
500				
700				
1000				