




**Case A
321.13**



Model No. : 221、222、321、322 SERIES

Outline :

- All series are liquid-filled.
- All series are stainless steel products with water proof, vibration proof, and closed structures which are capable against acidity, alkalinity and corrosion. With the features of durability and accuracy, it is also good for long time running.
- Special materials of movement and bourdon tube, have lasting durability.
- Specially it is applicable for corrosive fluid and strong fluctuation.

Features :

- Model** : 221、222 series. (Push Twist Removable Bezel-RB)
321、322 series. (Crimped on Bezel-CB)
- Type** : Pressure gauge、Vacuum gauge、Compound gauge.
- Nominal Size** : 40—50mm.
- Case** : Stainless steel AISI 304 supplied with LM、CBM、LBM mount type and blowout disk on the top.
- Tubing** : Stainless steel AISI 316.
- Movement** : Stainless steel AISI 304.
- Connection** : Stainless steel AISI 304、316, 1/8"、1/4", NPT、PT、PF.
- Pointer Type** : General.
- Accuracy** : $\pm 2\%$ F.S. (READ ANSI-B40.1 1985)
- Scale** : psi、bar、kPa、MPa、Kg/cm² etc. (Single or Dual Scale)

Note :

- LM : Lower Mount.
- CBM : Center Back Mount.
- LBM : Lower Back Mount.

Specifications :

Nominal size (mm)		Case	Connection	Model No.	Case Accessory
40	A	_____	NPT・PT・PF (1/8"・1/4")	321.13	_____
	D	_____		321.53	_____
		Fixed Strap			321.93
50	A	_____	NPT・PT・PF (1/8"・1/4")	322.13	_____
	D	_____		322.53	_____
		Fixed Strap			222.53
				322.93	U Bracket

Ranges (Kg/cm ²)	Socket	Tube	Accuracy (%F.S.)	Others
cmHg 76 cmHg 1 2 3 4 5 10 15 20 0~ 1 2 3 4 5 10 15 20 25 35 50 70 100 150 250 350 500 700 1000	5.5.304 5.5.316	5.5.316	± 2	<ul style="list-style-type: none"> • Case & Ring 304 St. St. • Window Glass Acrylic (ASA LENS) • Liquid Filled Glycerine Silicon